


PART NO: 16C4-B-2-B
 NO. OF SECTIONS: 2
 INDEXING: 45°
 CIRCUIT: C (SEE TRUTH TABLE)
 TYPE ACTION: NONSHORTING
 DETENT: STANDARD
 STOPS INSTALLED: NO
 TERMINALS: SCREW TYPE, HARDWARE SUPPLIED
 PHENOLIC OVAL KNOB: SUPPLIED
 MOUNTING HARDWARE: SUPPLIED



ELECTRICAL RATINGS:

- 15 A @ 125 VAC
- 5 A @ 250 VAC
- 3 A @ 600 VAC
- 5 A @ 30 VDC
- 1 A @ 125 VDC



DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
 CONTACT RESISTANCE: 10 MILLIOHMS MAX. INITIAL
 INSULATION RESISTANCE: 1000 MEGHOHMS, INITIAL

DECK	CONTACTS	POSITION							
		1	2	3	4	5	6	7	8
1	11 — — 12	X				X			
	12 — — 13		X				X		
	13 — — 14			X				X	
	14 — — 15				X				X
	15 — — 16	X				X			
	16 — — 17		X				X		
	17 — — 18			X				X	
	18 — — 11				X				X
	21 — — 22								
2	22 — — 23		X				X		
	23 — — 24			X				X	
	24 — — 25				X				X
	25 — — 26	X				X			
	26 — — 27		X				X		
	27 — — 28			X				X	
	28 — — 21				X				X

X DENOTES CONTACT CLOSURE

