

SHALLCO SERIES 26

Part Number: 2657C



General:

Meets requirements for 1 - 25 ampere switching of resistive loads to .75 power factor at voltages to 600 V AC and 250 VDC resistive loads

Electrical:

* Ratings:



- 25A/120 VAC
- 15A/600 VAC
- 20A/600 VAC (RESISTIVE)
- 3A/125 VDC
- 1A/250 VDC

- * Current carrying capacity: 25 amperes
- * Dielectric Withstanding Voltage: 2200 Vrms
- * Contact Resistance: Initial, 10 milliohms max.
- * Insulation Resistance: 100 Megohms min., initial

Mechanical:

- * Sections: 5 active
- * Positions: 2 Shaft will spring return to the center (rest) positions (See Truth Table and Operation)
- * Operation: Non-shorting
- Detent Type: Section 1 & 2 - Spring Return
- Detent Type: Section 3 & 4 - Slip Detent
- * Indexing: 45°
- * Rotational Life: 65,000 operations

Materials and Finishes:

- * Rotors and Stators: Thermoset Plastic, UL 94VO
- * Rotor contacts: Phosphor bronze
- * Stator contacts: Silver plated copper, screw type
- * Terminal hardware: silver plated brass
- * Exterior Metal: Steel with zinc chromate finish
- * Knob: thermoset phenolic

DECK	CONTACTS	POS.			
		TRIP	nat	nac	CLOSE
1	12O-I-I-O13				X
	16O-I-I-O17				X
2	21O-I-I-O28	X			
	24O-I-I-O25	X			
3	31O-I-I-O32		X	X	
	35O-I-I-O36		X	X	
4	42O-I-I-O43			X	X
	46O-I-I-O47			X	X
5	51O-I-I-O52	X	X		
	55O-I-I-O56	X	X		

