



## SHALLCO PART NUMBER 211-BB-6-375

DESCRIPTION: NO. OF DECKS: 2

NO OF POLES PER DECK: 1 NUMBER OF POSITIONS: 6

TYPE ACTION: NON SHORTING (BREAK BEFORE MAKE)

ANGLE OF THROW: 30°

## **ELECTRICAL**:

**CURRENT CARRY CAPACITY: 10 AMPS** 

CURRENT SWITCHING CAPACITY: UP TO 2 AMPS

CONTACT RESISTANCE: .005 OHMS INITIAL

INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL

DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

## MECHANICAL:

ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL

CW AND ONE FULL CCW ROTATION)

STOP TORQUE: 50 IN-LBS CONSTRUCTION: OPEN FRAME

WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS

DESCRIPTION

211-BB-6-375



308 COMPONENTS DRIVE SMITHFIELD, NC 27577 USA