



DESCRIPTION

SHALLCO PART NUMBER: 212-CB-16

- * NUMBER OF DECKS: 2
- * NUMBER OF POLES PER DECK: 1
- * NUMBER OF POSITIONS: 16 (STOP INSTALLED)
- * DETENT: STANDARD
- * ANGLE BETWEEN CONTACTS: 22-1/2°
- * SWITCHING: NONSHORTING
- * CURRENT CARRYING CAPACITY: 10 AMPERES
- * CURRENT SWITCHING CAPACITY: 2 AMPERES

- * CURRENT SWITCHING CAPACITY: 2 AMPERES
- * CONTACT RESISTANCE, INITIAL: 5 MILLIOHMS MAX.
- * CONTACT RESISTANCE, AFTER LIFE: 10 MILLIOHMS MAX.
- * INSULATION RESISTANCE: 50,000 MEGOHMS
- * DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
- * DIELECTRIC WITHSTANDING VOLTAGE, AFTER LIFE: 1000 VRMS
- * ROTATIONAL LIFE: 50,000 CYCLES (ONE CYCLE = ONE FULL CLOCKWISE AND ONE FULL COUNTER CLOCKWISE ROTATION)

DESCRIPTION

212-CB-16