



SHALLCO PART NUMBER 223-EB-24

DESCRIPTION:
 NO. OF DECKS: 2
 NO OF POLES PER DECK: 2
 NUMBER OF POSITIONS: 24 CONTINUOUS ROTATION
 TYPE ACTION: NON-SHORTING (BREAK BEFORE MAKE)
 ANGLE OF THROW: 15°

ELECTRICAL:
 CURRENT CARRY CAPACITY: 10 AMPS
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
 CONTACT RESISTANCE: .005 OHMS INITIAL
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:
 ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL
 CW AND ONE FULL
 CCW ROTATION)
 STOP TORQUE: 50 IN-LBS
 CONSTRUCTION: OPEN FRAME
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS
 (TORSION BAR DESIGN). EPOXY LAMINATE PANELS WITH .025
 SILVER HEADED CONTACTS, CDA 110 BASE AND GOLD
 FLASHING

DESCRIPTION
 223-EB-24