


# SHALLCO SERIES 16 SWITCH



PART NO: 16C4-B-2SR-D  
 NO. OF SECTIONS: 2  
 INDEXING: 45°  
 CIRCUIT: C (SEE CONTACT TABLE)  
 TYPE ACTION: NONSHORTING  
 DETENT: STANDARD  
 STOPS INSTALLED: NO (ADJUSTABLE FOR 1 OR 2 POSITIONS)  
 TERMINALS: SCREW TYPE, HARDWARE SUPPLIED  
 PHENOLIC PISTOL GRIP KNOB: SUPPLIED  
 MOUNTING HARDWARE: SUPPLIED



## ELECTRICAL RATINGS:

15 A @ 125 VAC  
 5 A @ 250 VAC  
 3 A @ 600 VAC  
 5 A @ 30 VDC  
 1 A @ 125 VDC



DECK	CONTACTS	POS		
		8	1	2
1	18 — 11	X		
	11 — 12		X	
	12 — 13			X
	14 — 15	X		
	15 — 16		X	
	16 — 17			X
2	28 — 21	X		
	21 — 22		X	
	22 — 23			X
	24 — 25	X		
	25 — 26		X	
	26 — 27			X

"X" DENOTES CONTACT CLOSURE

DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS  
 CONTACT RESISTANCE: 10 MILLIOHMS MAX. INITIAL  
 INSULATION RESISTANCE: 1000 MEGHOHMS, INITIAL

