

SHALLCO SERIES 16 SWITCH

PART NO: 16C4-B-1-A

NO. OF SECTIONS: 1

INDEXING: 45°

CIRCUIT: C (SEE TABLE

TYPE ACTION: NONSHORTING

DETENT: STANDARD

STOPS INSTALLED: NO

TERMINALS: SCREW TYPE, HARDWARE SUPPLIED

PHENOLIC POINTER KNOB: SUPPLIED

MOUNTING HARDWARE: SUPPLIED

ELECTRICAL RATINGS:



15 A @ 125 VAC

5 A @ 250 VAC

3 A @ 600 VAC

5 A @ 30 VDC

1 A @ 125 VDC



DECK	CONTACTS	POSITION							
		1	2	3	4	5	6	7	8
1	11 — 12	X				X			
	12 — 13		X				X		
	13 — 14			X				X	
	14 — 15				X				X
	15 — 16	X							X
	16 — 17		X						X
	17 — 18			X					X
	18 — 11				X				X

Contact Table

DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
CONTACT RESISTANCE: 10 MILLIOHMS MAX. INITIAL
INSULATION RESISTANCE: 1000 MEGHOHMS, INITIAL

