

DESCRIPTION

SHALLCO PART NUMBER: 241-CB-3

NUMBER OF DECKS: 2
 NUMBER OF POLES PER DECK: 4
 NUMBER OF POSITIONS: 3
 SWITCHING: NON-SHORTING (BREAK BEFORE MAKE)
 ANGLE OF THROW: 30°
 CURRENT CARRYING CAPACITY: 10 AMPERES
 CURRENT SWITCHING CAPACITY: 2 AMPERES
 CONTACT RESISTANCE, INITIAL: 5 MILLIOHMS MAX.
 CONTACT RESISTANCE, AFTER LIFE: 10 MILLIOHMS MAX.
 INSULATION RESISTANCE: 50,000 MEGOHMS
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
 DIELECTRIC WITHSTANDING VOLTAGE, AFTER LIFE: 1000 VRMS
 ROTATIONAL LIFE: 50,000 CYCLES (ONE CYCLE = ONE FULL
 CLOCKWISE AND ONE FULL COUNTER CLOCKWISE ROTATION)
 MOUNTING SCREWS SUPPLIED WITH SWITCH

DESCRIPTION


241-CB-3

REV A



308 COMPONENTS DRIVE
 SMITHFIELD, NC 27577 USA

TERMINALS DESIGNATIONS ARE FOR
 REFERENCE ONLY AND ARE SHOWN TO
 CLARIFY CONTACT TABLE



CONTACT TABLE

DECKS	TERMINALS	POSITION		
		1	2	3
1 AND 2	A COMMON	A1	A2	A3
	B COMMON	B1	B2	B2
	B COMMON	B1	B2	B2
1 AND 2	A COMMON	A1	A2	A3
	B COMMON	B1	B2	B2
	B COMMON	B1	B2	B2