



FUNDAMENTAL WIRING DIFFERENCES IN HIGH SIDE VERSUS LOW SIDE OPERATION

Main Terminals: 88 and 88a (No polarity restrictions)

SHALLCO INC.
 LOCAL: 919-934-3135
 TOLL FREE: 800-876-3135
 WWW.SHALLCO.COM

* Informational purposes only *

SHALLCO

308 COMPONENTS DRIVE, SMITHFIELD, NC 27577 USA

DO NOT SCALE DRAWING

TITLE: **BI-STABLE RELAY OPERATION**

MATERIAL: - FINISH: -

BLANK WEIGHT: - PART WEIGHT: -

SIZE **A** DWG. NO. **BI-STABLE RELAY** REV. **B**
 SHEET 1 OF 1

SCALE: 1:1 | FILENAME: Website Bi-Stable Relay Wiring 9-2-22 | WWW.SHALLCO.COM

	NAME	DATE
DRAWN	JRT	9-2-22
CHECKED		
ENG APPR.	RMF	9-2-22
MFG APPR.		
Q.A.		

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ± 1/32
 ANGULAR: MACH ± BEND ±
 TWO PLACE DECIMAL ± .010
 THREE PLACE DECIMAL ± .005

PROPRIETARY AND CONFIDENTIAL

This document contains proprietary data for products designed by Shallco, Inc., of Smithfield, NC. No disclosure; reproduction, or use of any part thereof may be made except by written permission.

REV.	DESCRIPTION	DATE	APP'D	REV.	DESCRIPTION	DATE	APP'D
	REVISIONS				REVISIONS		