



DESCRIPTION

- SHALLECO PART NUMBER: 111-CM 24
- NUMBER OF DECKS: 1
- NUMBER OF POLES PER DECK: 1
- NUMBER OF POSITIONS: 24 (ADJUSTABLE)
- DETENT: STANDARD
- ANGLE BETWEEN CONTACTS: 30°
- MOUNTING SCREWS SUPPLIED

SWITCHING: SHORTING (MAKE BEFORE BREAK)

- CURRENT CARRYING CAPACITY: 10 AMPERES
- CURRENT SWITCHING CAPACITY: 2 AMPERES
- CONTACT RESISTANCE, INITIAL: 5 MILLIOHMS MAX.
- CONTACT RESISTANCE, AFTER LIFE: 10 MILLIOHMS MAX.
- INSULATION RESISTANCE: 50,000 MEGOHMS
- DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
- DIELECTRIC WITHSTANDING VOLTAGE, AFTER LIFE: 1000 VRMS
- ROTATIONAL LIFE: 50,000 CYCLES (ONE CYCLE = ONE FULL CLOCKWISE AND ONE FULL COUNTER CLOCKWISE ROTATION)

DESCRIPTION

111-CM-24