



DESCRIPTION

SHALCO PART NUMBER: 112-CB-12

NUMBER OF DECKS: 1
 NUMBER OF POLES PER DECK: 1
 NUMBER OF POSITIONS: 12 (ADJUSTABLE)
 DETENT: STANDARD
 ANGLE BETWEEN CONTACTS: 22.5°

SWITCHING: NONSHORTING

CURRENT CARRYING CAPACITY: 10 AMPERES
 CURRENT SWITCHING CAPACITY: 2 AMPERES
 CONTACT RESISTANCE, INITIAL: 5 MILLIOHMS MAX.
 CONTACT RESISTANCE, AFTER LIFE: 10 MILLIOHMS MAX.
 INSULATION RESISTANCE: 50,000 MEGOHMS
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
 DIELECTRIC WITHSTANDING VOLTAGE, AFTER LIFE: 1000 VRMS
 ROTATIONAL LIFE: 50,000 CYCLES (ONE CYCLE = ONE FULL
 CLOCKWISE AND ONE FULL COUNTER CLOCKWISE ROTATION)

DESCRIPTION

112-CB-12



308 COMPONENTS DRIVE
 SMITHFIELD, NC 27577 USA

DRAWN P.DORMAN 2-19-09

SCALE 1 = 1

112-CB-12

SHEET 1 OF 1