



SHALCO PART NUMBER 112-DB-16A

DESCRIPTION:

NO. OF DECKS: 1
 NO OF POLES PER DECK: 1
 NUMBER OF POSITIONS: 16, ADJUSTABLE
 TYPE ACTION: NON-SHORTING (BREAK BEFORE MAKE)
 ANGLE OF THROW: 22.5°

ELECTRICAL:

VOLTAGE RATING: 125 VAC, 28 VDC
 CURRENT CARRY CAPACITY: 10 AMPS
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
 CONTACT RESISTANCE: .005 OHMS INITIAL
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:

ROTATIONAL LIFE: 50,000 CYCLES MIN.
 (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)
 STOP TORQUE: 50 IN-LBS
 CONSTRUCTION: OPEN FRAME
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS (TORSION BAR DESIGN), EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110 BASE AND GOLD FLASHING

DESCRIPTION

112-DB-16A

REV A

SHALCO 308 COMPONENTS DRIVE
 SMITHFIELD, NC 27577 USA