



SHALLCO PART NUMBER 121-DB-2

DESCRIPTION:
 NO. OF DECKS: 1
 NO OF POLES PER DECK: 2
 NUMBER OF POSITIONS: 2
 TYPE ACTION: NON-SHORTING (BREAK BEFORE MAKE)
 ANGLE OF THROW: 30°

ELECTRICAL:
 VOLTAGE RATING: 125 VAC, 28 VDC
 CURRENT CARRY CAPACITY: 10 AMPS
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
 CONTACT RESISTANCE: .005 OHMS INITIAL
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:
 ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)
 STOP TORQUE: 50 IN-LBS
 CONSTRUCTION: OPEN FRAME
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY
 WIPERS (TORSION BAR DESIGN): EPOXY
 LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS,
 CDA 110 BASE AND GOLD FLASHING

DESCRIPTION	121-DB-2
	
308 COMPONENTS DRIVE SMITHFIELD, NC 27577 USA	

--	--