



SHALLCO PART NUMBER 122-DB-11

DESCRIPTION:  
 NO. OF DECKS: 1  
 NO OF POLES PER DECK: 2  
 NUMBER OF POSITIONS: 9  
 TYPE ACTION: NONSHORTING  
 ANGLE OF THROW: 22.5°

ELECTRICAL:  
 CURRENT CARRY CAPACITY: 10 AMPS  
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS  
 CONTACT RESISTANCE: .005 OHMS INITIAL  
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL  
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:  
 ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)  
 STOP TORQUE: 50 IN-LBS  
 CONSTRUCTION: OPEN FRAME  
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS (TORSION BAR DESIGN). EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110 BASE AND GOLD FLASHING

DESCRIPTION	122-DB-9	DRAWN	P. DORRMAN	5-27-10
		SCALE	1X	
		308 COMPONENTS DRIVE SMITHFIELD, NC 27577 USA		
	122-DB-9	SHEET	1	OF 1