



SHALLCO PART NUMBER 211-BB-6

**DESCRIPTION:**

NO. OF DECKS: 2  
 NO. OF POLES PER DECK: 1  
 NUMBER OF POSITIONS: 6  
 TYPE ACTION: NON SHORTING (BREAK BEFORE MAKE)  
 ANGLE OF THROW: 30°

**ELECTRICAL:**

CURRENT CARRY CAPACITY: 10 AMPS  
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS  
 CONTACT RESISTANCE: .005 OHMS INITIAL  
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL  
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

**MECHANICAL:**

ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL  
 CW AND ONE FULL CCW ROTATION)  
 STOP TORQUE: 50 IN-LBS  
 CONSTRUCTION: OPEN FRAME  
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS  
 EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS

DESCRIPTION

211-BB-6