



DESCRIPTION

SHALCO PART NUMBER: 211-CB-9 OSD

NUMBER OF DECKS: 2
 NUMBER OF POLES PER DECK: 1
 NUMBER OF POSITIONS: 9
 SWITCHING: NON-SHORTING (BREAK BEFORE MAKE)
 ANGLE OF THROW: 22.5°
 CURRENT CARRYING CAPACITY: 10 AMPERES
 CURRENT SWITCHING CAPACITY: 2 AMPERES
 CONTACT RESISTANCE, INITIAL: 5 MILLIOHMS MAX.
 CONTACT RESISTANCE, AFTER LIFE: 10 MILLIOHMS MAX.
 INSULATION RESISTANCE: 50,000 MEGOHMS
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
 DIELECTRIC WITHSTANDING VOLTAGE, AFTER LIFE: 1000 VRMS
 ROTATIONAL LIFE: 50,000 CYCLES (ONE CYCLE = ONE FULL CLOCKWISE AND ONE FULL COUNTER CLOCKWISE ROTATION)

MOUNTING SCREWS SUPPLIED WITH SWITCH

DESCRIPTION

211-CB-9 OSD



308 COMPONENTS DRIVE
SMITHFIELD, NC 27577 USA

DRAWN P.DORMAN 1-12-15

SCALE 1 = 1

211-CB-9 OSD

SHEET 1 OF 1