



SHALLCO PART NUMBER 211-DB-5

DESCRIPTION:

NO. OF DECKS: 2
 NO OF POLES PER DECK: 1
 NUMBER OF POSITIONS: 5
 TYPE ACTION: NON-SHORTING (BREAK BEFORE MAKE)
 ANGLE OF THROW: 30°

ELECTRICAL:

CURRENT CARRY CAPACITY: 10 AMPS
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
 CONTACT RESISTANCE: .005 OHMS INITIAL
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:

ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)
 STOP TORQUE: 50 IN-LBS
 CONSTRUCTION: OPEN FRAME
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS (TORSION BAR DESIGN). EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110
 BASE AND GOLD FLASHING

DESCRIPTION	211-DB-5		DRAWN	P.DORMAN	3-11-05
			SCALE	1X	
 308 COMPONENTS DRIVE SMITHFIELD, NC 27577 USA			211-DB-5		
			SHEET 1 OF 1		