



SHALCO PART NUMBER 214-FB-6

**DESCRIPTION:**

- NO. OF DECKS: 1
- NO OF POLES PER DECK: 1
- NUMBER OF POSITIONS: 6
- TYPE ACTION: NON-SHORTING
- ANGLE OF THROW: 12°

**ELECTRICAL:**

- CURRENT CARRY CAPACITY: 10 AMPS
- CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
- CONTACT RESISTANCE: .005 OHMS INITIAL
- INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
- DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

**MECHANICAL:**

- ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)
- STOP TORQUE: 50 IN-LBS
- CONSTRUCTION: OPEN FRAME
- WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110 BASE AND GOLD FLASHING

DESCRIPTION

**214-FB-6**