



SHALLCO PART NUMBER 221-DM-24

DESCRIPTION:

NO. OF DECKS: 2
 NO OF POLES PER DECK: 2
 NUMBER OF POSITIONS: 24 (CONTINUOUS ROTATION)
 TYPE ACTION: SHORTING (MAKE BEFORE BREAK)
 ANGLE OF THROW: 15°

ELECTRICAL:

CURRENT CARRY CAPACITY: 10 AMPS
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
 CONTACT RESISTANCE: .005 OHMS INITIAL
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:

ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)
 STOP TORQUE: 50 IN-LBS
 CONSTRUCTION: OPEN FRAME
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS (TORSION BAR DESIGN). EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110 BASE AND GOLD FLASHING

| DESCRIPTION |
|-------------|
| 221-DM-24 |


SHALLCO
 309 COMPONENTS DRIVE
 SMITHFIELD, NC 27577
 USA