

SHALLECO PART NUMBER: 241-CB-2

- NUMBER OF DECKS: 2
- NUMBER OF POLES PER DECK: 4
- NUMBER OF POSITIONS: 2
- SWITCHING: NON-SHORTING (BREAK BEFORE MAKE)
- ANGLE OF THROW: 30°
- CURRENT CARRYING CAPACITY: 10 AMPERES
- CURRENT SWITCHING CAPACITY: 2 AMPERES
- CONTACT RESISTANCE, INITIAL: 5 MILLIOHMS MAX.
- CONTACT RESISTANCE, AFTER LIFE: 10 MILLIOHMS MAX.
- INSULATION RESISTANCE: 50,000 MEGOHMS
- DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
- DIELECTRIC WITHSTANDING VOLTAGE, AFTER LIFE: 1000 VRMS
- ROTATIONAL LIFE: 50,000 CYCLES (ONE CYCLE = ONE FULL CLOCKWISE AND ONE FULL COUNTER CLOCKWISE ROTATION)
- MOUNTING SCREWS SUPPLIED WITH SWITCH


DESCRIPTION

241-CB-2



308 COMPONENTS DRIVE
SMITHFIELD, NC 27577 USA

VIEW A - A



TERMINALS DESIGNATIONS ARE FOR REFERENCE ONLY AND ARE SHOWN TO CLARIFY CONTACT TABLE

DECKS	TERMINALS	POSITION	
		1	2
1 AND 2	A COMMON		
	B COMMON		
	C COMMON		
	D COMMON		
	A1		
	A2		
	B1		
	B2		

CONTACT TABLE