

SHALLCO PART NUMBER 241-DB-4

DESCRIPTION:


- NO. OF DECKS: 2
- NO OF POLES PER DECK: 4
- NUMBER OF POSITIONS: 4
- TYPE ACTION: SHORTING (BREAK BEFORE MAKE)
- ANGLE OF THROW: 30°
- MOUNTING: TWO HOLE

ELECTRICAL:

- CURRENT CARRY CAPACITY: 10 AMPS
- CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
- CONTACT RESISTANCE: .005 OHMS INITIAL
- INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
- DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:

- ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)
- STOP TORQUE: 50 IN-LBS
- CONSTRUCTION: OPEN FRAME
- WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS (TORSION BAR DESIGN), EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110
- BASE AND GOLD FLASHING



PIN LOCATIONS
DESIGNATION FOR REFERENCE ONLY.
(CONTACT PANEL IS NOT MARKED).

CONTACTS	POSITION			
	1	2	3	4
A	A1	A2	A3	A4
B	B1	B2	B3	B4
C	C1	C2	C3	C4
D	D1	D2	D3	D4

DESCRIPTION	241-DB-4	REV A
308 COMPONENTS DRIVE SMITHFIELD, NC 27577 USA		