



SHALLCO PART NUMBER 512-EM-32

DESCRIPTION:

NO. OF DECKS: 5  
 NO OF POLES PER DECK: 1  
 NUMBER OF POSITIONS: 32, CONTINUOUS ROTATION  
 TYPE ACTION: SHORTING (MAKE BEFORE BREAK)  
 ANGLE OF THROW: 11-1/4°

ELECTRICAL:

CURRENT CARRY CAPACITY: 10 AMPS  
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS  
 CONTACT RESISTANCE: .005 OHMS INITIAL  
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL  
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:

ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)  
 STOP TORQUE: 50 IN-LBS  
 CONSTRUCTION: OPEN FRAME  
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS (TORSION BAR DESIGN). EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110 BASE AND GOLD FLASHING

DESCRIPTION		512-EM-32	
 <b>SHALLCO</b> 308 COMPONENTS DRIVE SMITHFIELD, NC 27577 USA		SCALE	1X
		SHEET	1 OF 1