



6-32 TAPPED HOLE (4 PLCS)

SHALLCO PART NUMBER 581-EB-2

DESCRIPTION:
 NO. OF DECKS: 5
 NO OF POLES PER DECK: 8
 NUMBER OF POSITIONS: 2
 TYPE ACTION: NONSHORTING (BREAK BEFORE MAKE)
 ANGLE OF THRDW: 30°

ELECTRICAL:
 CURRENT CARRY CAPACITY: 10 AMPS
 CURRENT SWITCHING CAPACITY: UP TO 2 AMPS
 CONTACT RESISTANCE: .005 OHMS INITIAL
 INSULATION RESISTANCE: 50,000 MEGOHMS INITIAL
 DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS INITIAL

MECHANICAL:
 ROTATIONAL LIFE: 50,000 CYCLES MIN. (ONE CYCLE=ONE FULL CW AND ONE FULL CCW ROTATION)
 STOP TORQUE: 50 IN-LBS
 CONSTRUCTION: OPEN FRAME
 WIPERS AND CONTACT PANELS: DUAL SILVER ALLOY WIPERS (TORSION BAR DESIGN). EPOXY LAMINATE PANELS WITH .025 SILVER HEADED CONTACTS, CDA 110 BASE AND GOLD FLASHING

TERMINALS	POSITION	
	1	2
A1-O1	⊗	⊗
A2-O2	⊗	⊗
A3-O3	⊗	⊗
A4-O4	⊗	⊗
A5-O5	⊗	⊗
A6-O6	⊗	⊗
A7-O7	⊗	⊗
A8-O8	⊗	⊗

THE VIEW SHOWN ABOVE WOULD BE THE CONTACT PANEL AS VIEWED FROM THE REAR OF THE SWITCH. THE TERMINAL DESIGNATIONS ARE FOR LOCATION REFERENCE ONLY AND ARE TYPICAL FOR ALL DECKS. (DECKS TERMINALS ARE NOT MARKED)

DESCRIPTION	581-EB-2	DRAWN	P. DORRMAN	2-7-11
SCALE	1X			
308 COMPONENTS DRIVE SMITHFIELD, NC 27577 USA		SHALLCO		
581-EB-2		SHEET	1	OF 1