SHALLCO SERIES 26
Part Number: 2636B

General:
Meets requirements for 1 - 25 ampere switching of resistive loads to .75 power factor at voltages to 600 V AC and 250 VDC resistive loads





Electrical:
* Ratings:

25A/120 VAC
15A/600 VAC
20A/600 VAC (RESISTIVE)
3A/125 VDC
1A/250 VDC

* Current carrying capacity: 25 amperes
* Dielectric Withstanding Voltage: 2200 Vrms
* Contact Resistance: Initial, 10 milliohms max.
* Insulation Resistance: 100 Megohms min., initial



ESCUTCHEON PLATE



Mechanical:
* Sections: 1
* Positions: 2, Spring Return CCW
* Indexing: 45°
* Rotational Life: 65,000 operations



MOUNTING HOLE DETAIL

Materials and Finishes:
* Rotors and Stators: Thermoset Plastic, UL 94VO
* Rotor contacts: Phosphor bronze
* Stator contacts: Silver plated copper, screw type
* Terminal hardware: silver plated brass
* Exterior Metal: Steel with zinc chromate finish
* Knob: thermoset phenolic



DESCRIPTION 2636B

SHALLCO
308 COMPONENTS DRIVE
SMITHFIELD, NC 27577 USA

REV. -