SHALLCO SERIES 26
Part Number: 2636D 125VDCACC

SHALLCO
308 COMPONENTS DRIVE
SMITHFIELD, NC 27577 USA

General:
Meets requirements for 1 - 25 ampere switching of resistive loads to .75 power factor at voltages to 600 VAC and 250 VDC resistive loads

Electrical:
* Voltages: 250 V DC, 600 VAC
* Current carrying capacity: 25 amperes
* Dielectric Withstanding Voltage: 2200 Vrms
* Contact Resistance: Initial, 10 milliohms max.
* Insulation Resistance: 100 Megohms min., initial

* Switch is supplied with a lighted escutcheon plate:
  Input voltage: 18 to 140 VDC
  Wiring: As shown

Mechanical:
* Sections: 2
* Positions: 2, Spring Return to vertical (Off)
* Indexing: 45°
* Rotational Life: 65,000 operations

Materials and Finishes:
* Rotors and Stators: Thermoset Plastic, UL 94VO
* Rotor contacts: Phosphor bronze
* Stator contacts: Silver plated copper, screw type
* Terminal hardware: silver plated brass
* Exterior Metal: Steel with zinc chromate finish
* Knob: thermoset phenolic



MOUNTING HOLE DETAIL



	POSITION	
CONTACT	NORMAL	CLOSE
12 - 13		X
16 - 17		X