SHALLCO SERIES 26
Part Number: 26803B

General:

Meets requirements for 1 - 25 ampere switching of resistive loads to .75 power factor at voltages to 600 V AC and 250 V DC resistive loads

Electrical:

* Ratings:
  25A/120 VAC
  15A/600 VAC
  20A/600 VAC (RESISTIVE)
  3A/125 VDC
  1A/250 VDC

* Current carrying capacity: 25 amperes
* Dielectric Withstanding Voltage: 2200 Vrms
* Contact Resistance: Initial, 10 milliohms max.
* Insulation Resistance: 100 Megohms min., initial

Mechanical:

* Sections: 3
* Positions: 8, Adustable
* Indexing: 45°
* Rotational Life: 65,000 operations

Materials and Finishes:

* Rotors and Stators: Thermoset Plastic, UL 94VO
* Rotor contacts: Phosphor bronze
* Stator contacts: Silver plated copper, screw type
* Terminal hardware: silver plated brass
* Exterior Metal: Steel with zinc chromate finish
* Knob: thermoset phenolic



DECK	CONTACTS	POSITIONS 1	2	3	4	5	6	7	8
1	11								
	12	X				X			
	13		X				X		
	14			X				X	
	15				X				X
	16	X				X			
	17		X				X		
	18			X				X	
2	21								
	22	X				X			
	23		X				X		
	24			X				X	
	25				X				X
	26	X				X			
	27		X				X		
	28			X				X	
3	31								
	32	X				X			
	33		X				X		
	34			X				X	
	35				X				X
	36	X				X			
	37		X				X		
	38			X				X	





DESCRIPTION

26803B

308 COMPONENTS DRIVE
SMITHFIELD, NC 27577 USA

TERMINAL SCREW TIGHTENING TORQUE: : 8 IN-LBS.