PART NUMBER 3A01-2

GENERAL: MEETS THE REQUIREMENTS FOR 10 TO 30 AMPERES OF SWITCHING OF RESISTIVE LOADS TO .75 POWER FACTOR AT VOLTAGES TO 480 VAC AND 250 VDC

ELECTRICAL:
VOLTAGE: 480 VAC, 250 VDC
CARRYING CAPACITY: 45 AMPERES SWITCHING CAPACITY: UP TO 30 AMPERES
DIELECTRIC WITHSTANDING VOLTAGE: 2500 VRMS INITIAL
CONTACT RESISTANCE: 10 MILLIOHMS MAX. (4 MILLIOHMS AVERAGE)
INSULATION RESISTANCE: 1000 MEGHOHMS MIN. INITIAL

MECHANICAL:
POLES: 1 POSITIONS: 2
INDEXING: 90° CONTACTS: BREAK BEFORE MAKE
TERMINAL TYPE: SCREW CONSTRUCTION: CLOSED

SUPPLIED WITH MOUNTING HARDWARE, TERMINAL SCREWS, AND KNOB

KNOB

CIRCUIT





DECK	CONTACTS	POS. 1	POS. 2
1	1 ○—⊣⊢—○ 2		X







MOUNTING HOLE DETAIL

DESCRIPTION

3A01-2

DRAWN	P. DORMAN	4-4-06
SCALE: .5X		
A	3A01-2	
SHEET 1 OF 1		

SHALLCO

308 COMPONENTS DRIVE
SMITHFIELD, NC 27577 USA