

DESCRIPTION

SHALLCO PART NUMBER: 441-CB-2

NUMBER OF DECKS: 4
NUMBER OF POLES PER DECK: 4
NUMBER OF POSITIONS: 2
SWITCHING: NON-SHORTING (BREAK BEFORE MAKE)
ANGLE OF THROW: 30°
CURRENT CARRYING CAPACITY: 10 AMPERES
CURRENT SWITCHING CAPACITY: 2 AMPERES
CONTACT RESISTANCE, INITIAL: 5 MILLIOHMS MAX.
CONTACT RESISTANCE, AFTER LIFE: 10 MILLIOHMS MAX.
INSULATION RESISTANCE: 50,000 MEGOHMS
DIELECTRIC WITHSTANDING VOLTAGE: 1500 VRMS
DIELECTRIC WITHSTANDING VOLTAGE, AFTER LIFE: 1000 VRMS
ROTATIONAL LIFE: 50,000 CYCLES (ONE CYCLE = ONE FULL CLOCKWISE AND ONE FULL COUNTER CLOCKWISE ROTATION

MOUNTING SCREWS SUPPLIED WITH SWITCH

VIEW A - A



TERMINALS DESIGNATIONS ARE FOR REFERENCE ONLY AND ARE SHOWN TO CLARIFY TRUTH TABLE

TRUTH TABLE

DECKS	TERMINALS	POSITION 1	POSITION 2
1 THRU 4	A COMMON — A1	X	
	A COMMON — A2		X
	B COMMON — B1	X	
	B COMMON — B2		X
	C COMMON — C1	X	
	C COMMON — C2		X
	D COMMON — D1	X	
	D COMMON — D2		X

APP'D	DATE	DESCRIPTION	LTR

REVISIONS

DESCRIPTION: 441-CB-2

MATERIAL: SHALLCO SERIES C

SHALLCO

308 COMPONENTS DRIVE
SMITHFIELD, NC 27577 USA

DRAWN	P.DORMAN	9-13-02
CHECKED		
APPROVED	P.DORMAN	9-13-02
SCALE	1 = 1	
A	441-CB-2	REV. -
SHEET 1 OF 1		